

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

### 1 Identification

- · Product identifier
- · Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION
- Relevant identified uses of the substance or mixture and uses advised against:
- : For use in flushing of DTG Printers, ink lines, print heads, etc. This solution can be used for Long Term Storage of your printer.
- · Product description

Clear Solution designed for flushing and long term storage of a Direct to Garment printer.

- · Details of the supplier of the safety data sheet:
- Manufacturer/Supplier:

Image Armor, LLC 220 First Dr. NE

New Philadelphia, OH 44663

Phone: 877-673-4377 Fax: 330-2676-7437

www.imagearmorinks.com

Emergency telephone number: Image Armor LLC - 877-673-4377 Brian Walker - 330-934-0524

### 2 Hazard(s) identification

· Classification of the substance or mixture:



GHS08 Health hazard

STOT RE 2 H373 May cause damage to the central nervous system, the kidneys and the heart through prolonged or repeated exposure.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS08

- Signal word: Warning
- · Hazard-determining components of labeling:

Ethylene glycol

· Hazard statements:

Causes eye irritation.

May cause damage to the central nervous system, the kidneys and the heart through prolonged or repeated exposure.

· Precautionary statements:

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Get medical advice/attention if you feel unwell.

(Contd. on page 2)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 07/21/2015 Issue date 07/21/2015

#### Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 1

· Hazard(s) not otherwise classified (HNOC): None known

## Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Components:				
	Ethylene glycol STOT RE 2, H373;	5-10%		
CAS: 112-34-5 RTECS: KJ 9100000	Diethylene Glycol Monobutyl Ether ◆ Eye Irrit. 2, H319; Flam. Liq. 4, H227	1-5%		
CAS: 102-71-6	Triethanolamine, TEA  ♦ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	1-5%		

### 4 First-aid measures

- · Description of first aid measures:
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

### 5 Fire-fighting measures

- · Extinguishing media:
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture:

Decomposition may produce oxides of carbon, nitrogen, sulfur, hydrocarbons, fumes and smoke.

- · Advice for firefighters:
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling
- · Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities:
- · Storage
- · Requirements to be met by storerooms and receptacles:

Do not store in direct sunlight. Keep from freezing. Keep out of reach of children.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s): No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data: see section 7.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

- · Control parameters:
- · Components with occupational exposure limits:

#### 107-21-1 Ethylene glycol

TLV | Short-term value: NIC-127\* mg/m3

Long-term value: NIC-10\*\* NIC-63.5\* mg/m³, NIC-25\* ppm

Ceiling limit value: (100) mg/m³

(H); \*inh. fraction + vapor,P:\*\*inh. fraction, H

#### 112-34-5 Diethylene Glycol Monobutyl Ether

TLV Long-term value: 67.5\* mg/m³, 10\* ppm \*Inhalable fraction and vapor

## 102-71-6 Triethanolamine, TEA

TLV Long-term value: 5 mg/m<sup>3</sup>

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment: Not required.
- Protection of hands:



Protective gloves

· Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection:



Tightly sealed goggles

· Body protection:



Protective work clothing

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Clear to hazy

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

### Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

· Odor: Slight

· *Odor threshold:* Not determined.

· pH-value @ 20 °C (68 °F): 8

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:

Flash point:

Flammability (solid, gaseous):

Ignition temperature:

Not determined.

>100 °C (>212 °F)

111 °C (232 °F)

Not applicable.

225 °C (437 °F)

• Decomposition temperature: Not determined.

· Auto igniting: Product is not self-igniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

 Lower:
 3.2 Vol %

 Upper:
 53.0 Vol %

 ⋅ Vapor pressure @ 20 °C (68 °F):
 0.1 hPa

· Density:

Relative density:Not determined.Vapor density:Not determined.Evaporation rate:Not determined.

· Solubility in / Miscibility with:

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents:10.0 %VOC content:10.0 %Solids content:5.0 %

• Other information: No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided:

Oxides of carbon, nitrogen, hydrocarbons, fumes, and smoke

- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Acids, bases and oxidizers
- · Incompatible materials: Incompatible or can react with acids, bases and oxidizers.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

### 11 Toxicological information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
107-21-1 I	107-21-1 Ethylene glycol				
Oral	LD50	5840 mg/kg (rat)			
Dermal	LD50	9530 mg/kg (rabbit)			
Inhalative	LC50/96 hours	38.109 mg/l (Trout)			
	LC50/48 hrs	16.103 mg/l (daphnia)			
112-34-5 I	112-34-5 Diethylene Glycol Monobutyl Ether				
Oral	LD50	5660 mg/kg (rat)			
Dermal	LD50	4000 mg/kg (rabbit)			
102-71-6	102-71-6 Triethanolamine, TEA				
Oral	LD50	5530 mg/kg (rat)			
		2200 mg/kg (rabbit)			
	LD50 Oral	2200 ml/kg (Guinea Pig)			
		5846 ml/kg (mouse)			
Dermal	LD50	>22500 mg/kg (rabbit)			

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye:

Irritating effect.

Causes serious eye irritation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories:

· IARC (International Agency for Research on Cancer):	
102-71-6 Triethanolamine, TEA	3
· NTP (National Toxicology Program):	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	

### 12 Ecological information

· Toxicity:

	· <b>·</b>
· Aqua	tic toxicity:
107-2	1-1 Ethylene glycol
EC50	3.536 mg/l (Green algae)
102-7	1-6 Triethanolamine, TEA
EC50	609.98 mg/l (daphnia)

· Persistence and degradability: No further relevant information available.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

#### Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment:
- · **PBT**: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

· UN-Number:

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name:

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es):

· DOT, ADR, ADN, IMDG, IATA

· Class: Non-Regulated Material

· Packing group:

· **DOT, ADR, IMDG, IATA** Non-Regulated Material

• Environmental hazards: Not applicable. Special precautions for user: Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· UN "Model Regulation": Non-Regulated Material

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

107-21-1 Ethylene glycol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 07/21/2015 Reviewed on 07/21/2015

Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

· California Proposition 65:

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

Carcinogenic categories:

EPA (Environmental Protection Agency):

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

107-21-1 Ethylene glycol

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS08

- · Signal word Warning
- Hazard-determining components of labeling:

Ethylene glycol

· Hazard statements

Causes eye irritation.

May cause damage to the central nervous system, the kidneys and the heart through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Get medical advice/attention if you feel unwell.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(a) and GHS Rev 03.

Reviewed on 07/21/2015 Issue date 07/21/2015

Trade name: IMAGE ARMOR DTG INK FLUSHING SOLUTION

· State Right to Know		
CAS: 107-21-1 RTECS: KW 2975000	Ethylene glycol STOT RE 2, H373;	5-10%
CAS: 112-34-5 RTECS: KJ 9100000	Diethylene Glycol Monobutyl Ether ◆ Eye Irrit. 2, H319; Flam. Liq. 4, H227	1-5%
CAS: 102-71-6	Triethanolamine, TEA  ♦ Skin Irrit. 2, H315; Eye Irrit. 2B, H320	1-5%
All ingredients are liste	d.	

<sup>·</sup> Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 6 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision 07/21/2015 / 1
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 4: Flammable liquids, Hazard Category 4

Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106